

STAINLESS STEEL WIRE BASKET DRAWERS

NOTE: The screws provided are suited to 16mm timber/melamine board. Please use alternative screws for other surfaces.


GENERAL CARE

Stainless steel wire basket-warm soapy water. Zinc plated slides: Keep slides dry and wipe down with damp cloth and then wipe them dry. Avoid contact with water and other corrosive materials. If you require stainless steel slides, please contact us for a quote.

BOTTOM MOUNT SLIDES - WITH HOOK & BOTTOM MOUNT BRACKET (SLF.450)

450mm zinc plated full extension ball bearing slides, bottom mounted/weight capacity 20-40kgs*

- These slides are for fixed shelf cabinets.
- Minimum width = basket width + slides 29mm (ie, 2 x 14.5mm).
- Minimum height = basket height + slide bottom gap 20mm
- * Standard weight capacity 20kgs but if fitted with thread, washer and self-locking nut, you can store up to 40kgs. These additional fittings are not supplied.



STEP 1: Place slides on fixed shelf (if adjustable you will need to lock it down) as you require.



STEP 2: Place basket onto the slides. Position it 3 spaces back from the front (pictured). Mark your screw holes.



STEP 3: Remove basket & slides. Drill holes and install the slides. Clip the basket into the small hooks as pictured. Ensure slides are not extended and press down firmly.

STEP 4: If adjustment is required, loosen the screws and adjust in the slotted holes.



TIPS & TROUBLESHOOTING

- (1) Set back – The closer to the front the better, but position according to your needs.
- (2) Slides feel "tight": check that slides are "square" and parallel - measure your screws the distance between all screws, including diagonal, they should be equal distance.
- (3) Make sure the hook is clipped in the bottom wire and in the same position on the RHS and LHS.